540,182

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 8 July 2004 (08.07.2004)

PCT

(10) International Publication Number WO 2004/057673 A1

(51) International Patent Classification7: 23/498, 23/66, 23/31

H01L 23/64,

(21) International Application Number:

PCT/IB2003/006109

(22) International Filing Date:

22 December 2003 (22.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 02080670.9

23 December 2002 (23.12.2002)


- (71) Applicants (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). AGENCY FOR SCIENCE, TECHNOLOGY AND REASEARCH [SG/SG]; 30 Biopolis Street, #09-02, Matrix, Singapore 138668 (SG).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ROTARU, Mihai, D. [RO/SG]; c/o 11 Science Park Road, Science Park II,

117685 Singapore (SG). WEEKAMP, Johannus, W. [NL/NL]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL).

- (74) Agent: DUIJVESTIJN, Adrianus, J.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN. MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ELECTRONIC DEVICE AND USE THEREOF



(57) Abstract: The electronic device (100) comprises a semiconductor element (1) (e.g. a transistor), an encapsulation (5) and an electrically conductive layer (3) with a first and a second contact pad (11,12), used as signal pads, and a third contact pad (13) used as ground pads. Due to the shape of the contact pads (11,12,13), the spacing (200) is continuous, with a small entrance in between of the first and second contact pads (11,12). Consequently, the parasitic inductance is reduced and the device (100) is suitable for use at frequencies below and above 30 GHz, particularly up to 40 GHz.

WO 2004/057673 A1



Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.